

SPECIFICATIONS

SHERIDEN

Widths:	4.57m, 3.66m, 2.74m, 1.83m & 0.91m (15', 12', 9', 6' & 3')	Largeurs:	4,57m, 3,66m, 2,74m, 1,83m & 0.91m	Breiten:	4,57m, 3,66m, 2,74m, 1,83m & 0.91m
Repeat:	Cameo 31cm (12.20") Straight Match Pindot 5cm (1.96") Straight Match Runner 15cm (5.90")	Raccord:	Cameo 31cm Raccord Droit Pindot 5cm cm Raccord Droit Runner 15cm	Rapport:	Cameo 31cm Seite an Seite Pindot 5cm cm Seite an Seite Runner 15cm
Pile Yarn:	80% Wool (moth resistant) / 20% Nylon	Composition du fil:	80% Laine (résistant aux mites) / 20% Nylon	Polzusammensetzung:	80% Schurwolle (mottenresistent) / 20% Nylon
Total Pile Weight:	1255g/m ² (37.05 oz/yd ²) +/-10%	Poids total de velours:	1255g/m ² +/-10%	Poleinsatzgewicht:	1255g/m ² +/-10%
Pile Height:	6.35mm (0.25")	Hauteur de velours:	6,35mm	Polhöhe:	6,35mm
Pitch:	27.56 per DM (7 per inch)	Serrage chaîne:	27,56 par 10cm	Kettdichte:	27,56 pro 10cm
Rows:	35.43 per DM (9 per inch)	Serrage trame:	35,43 par 10cm	Schussdichte:	35,43 pro 10cm
Suitability:	Heavy Contract	Qualité:	Usage commercial intensif	Qualität:	Starke Anwendung im Objektbereich

Please note:

Carpet should be professionally laid according to BS 5325 ISO13746:2000 using good quality underlay.

A noter:

Toute moquette doit être posée selon la norme BS 5325 ISO 13746:2000 en utilisant une thibaude de bonne qualité.

Bemerkung:

Teppichboden sollte gemäß BS 5325 ISO 13746:2000 mit einer qualitativ hochwertigen Teppich-Unterlage verlegt werden.

EN 14041



ulsterTM
www.ulstercarpets.com